

CX802RGW

Overview

CX802RGW terminal devices are designed for fulfilling FTTH and triple play service demand of fixed network operators or cable operators. These boxes are based on the mature Gigabit EPON technology, which have high ratio of performance to price, and the technology of 802.11n WiFi (2T2R), Layer 2/3. They are highly reliable and easy to maintain, with guaranteed QoS for different service. And they are fully compliant with technical regulations such as IEEE802.3ah and technical requirement of EPON Equipment from China Telecom.

Special Features

- ▶ Plug and play, features auto-detecting, auto-configuration, and auto firmware upgrade, etc.
- ▶ Integrated OAM remote configuration and maintenance function.
- ▶ Support rich QinQ VLAN functions and IGMP Snooping multicast features.
- ▶ Fully compatibility with OLT based on Broadcom/PMC/Cortina chipset.
- ▶ Support 802.11n WiFi(2T2R) function.
- ▶ Support NAT, Firewall function.
- ▶ Support IPv4 and IPv6 dual stack.
- ▶ The WAN port supports bridge, router and bridge/router mixed mode.



Art No : CX802RGW

Material : ABS Plastic

Size : 185mm*122mm*33mm(L*W*H)

Weight : 0.25kg

Color : White

Description : 1*100M+1*1000M Ethernet routing ONU, Compatible with Huawei,ZTE,Fiberhome,Dasan, Alcate OLT

Technical parameters

Technical Items	Description
	CX802EW
Main chip	Realtek

CX802RGW

<u>Technical Items</u>	<u>Description</u>
PON interface	1 EPON interface, SC single-mode/single-fiber, symmetric 1.25Gbps
PON Port Type	BOSA
Wavelength	EPON Tx 1310nm, EPON Rx 1490nm
Sensitivity	<-27dBm(PX20+)
Overload	>-3dBm(PX20+)
Optical interface	SC/PC connector
WLAN	Compliant with IEEE802.11b/g/n, 300Mbps, 2T2R One internal antenna and one external antenna
WLAN throughput	100Mbps @ 40users, 1518bytes, no-encryption 107Mbps @ 40users, 512bytes, encryption
LAN interface	1*10/100/1000Mbps+1*10/100Mbps auto adaptive Ethernet interfaces, RJ45
Indicators	8 indicators, for status of power supply, PON, LAN ,WiFi.
DC power supply	+12V, external AC-DC power adaptor
Power consumption	≤9W
Operating condition	Operating temp: -5~+55°C Operating humidity:10~90%(non-condensed)
Storing condition	Storing temp: -30~+60°C Storing humidity:10~90%(non-condensed)
Dimension	185mm*33mm*122mm (W*H*D)
Net weight	0.25Kg