

## CX600G1

### Overview

CX600G series GPON OLT products are 1U height 19 inch rack mount products. The features of the OLT are small, convenient, flexible, easy to deploy, high performance. It is appropriate to be deployed in compact room environment. The OLTs can be used for "Triple-Play", VPN, IP Camera, Enterprise LAN and ICT applications.

### Special Features

- ▶ **Satisfactory standard**  
Meet ITU-T G984/G.988 standard  
Meet China's relevant GPON standards
- ▶ **L3 OLT**  
Support static route RIP v1/v2, OSFP v2
- ▶ **Easy to manage**  
Friendly EMS/Web/Telnet/CLI management  
CLI command style similar to mainstream manufacturers  
Support APP management
- ▶ **Fully open platform**  
Open to any brand of ONT
- ▶ **High performance cost**  
1U height compact design  
Adopt mainstream chip scheme



| Item              |                            | CX600G1                                   |
|-------------------|----------------------------|---|
| Chassis           | Rack                       | 1U 19 inch standard box                   |
| 1000M Uplink Port | QTY                        | 16  |
|                   | Copper                     | 8*10/100/1000M auto-negotiation           |
|                   | SFP(SFP+)<br>(independent) | 6*SFP and 2SFP+ slots (SFP+ is 10GE port) |

## CX600G1

| Item                   |                          | CX600G1   |
|------------------------|--------------------------|---|
| GPON Port              | QTY                      | 8   |
|                        | Physical Interface       | SFP Slots   |
|                        | Connector Type           | Class B+/C+   |
|                        | Max splitting ratio      | 1:128   |
| Management Ports       |                          | 1*10/100BASE-T out-band port, 1*CONSOLE port  |
| PON Port Specification | Transmission Distance    | 20KM  |
|                        | GPON port speed          | Upstream 1.244G, Downstream 2.488G  |
|                        | Wavelength               | TX 1490nm, RX 1310nm  |
|                        | Connector                | SC/PC   |
|                        | Fiber Type               | 9/125μm SMF   |
|                        | TX Power                 | +1~+5dBm  |
|                        | Rx Sensitivity           | -28dBm  |
|                        | Saturation Optical Power | -8dBm   |
| Management Mode        |                          | SNMP, Telnet, CLI, WEB  |
| Management Function    |                          | <p>Fan Group Detecting;</p> <p>Port Status monitoring and configuration management;</p> <p>Layer2 switch configuration such as VLAN, Trunk,RSTP,IGMP,QOS, etc;</p> <p>EPON management function: DBA,ONU authorization, ACL,QOS,etc;</p> <p>Online ONU configuration and management;</p> <p>User management;</p> <p>Alarm management</p> |

## CX600G1

| Item          | CX600G1  |
|---------------|--|
| Layer2 Switch | <p>16K Mac address;<br/> Support port VLAN and protocol VLAN;<br/> Support 4096 VLANs;<br/> Support VLAN tag/Un-tag ,VLAN transparent transmission, QinQ;<br/> Support storm control based on port;<br/> Support port isolation;<br/> Support port rate limitation;<br/> Support 802.1D and 802.1W;<br/> Support static LACP.<br/> QOS based on port,VID,TOS and MAC address.<br/> Access control list.<br/> IEEE802.x flow control.<br/> Port stability statistic and monitoring.</p>   |
| Multicast     | <p>IGMP snooping;<br/> 256 IP Multicast Groups;</p>  |
| DHCP          | <p>DHCP server;<br/> DHCP relay;<br/> DHCP snooping;</p>   |
| Layer 3Route  | <p>Arp proxy;<br/> Static route;<br/> 512 hardware Subnet Routes;<br/> 1024 hardware Host Routes;</p>  |
| GPON Function | <p>Tcont dba;<br/> Gempport traffic;<br/> In compliant with ITUT984.xstandard;<br/> Up to 20KM transmission Distancec;<br/> Support data encryption, multi-cast, port VLAN, separation,RSTP,etc;<br/> Support ONU auto-discovery/link detection/ remote upgrade of software;<br/> Support VLAN division and user separation to avoid broadcast storm;<br/> Support power-off alarm function,easy for link problem detection;<br/> Support broadcasting storm resistance function;<br/> Support port isolation between different ports;<br/> Support ACL and SNMP to configure data packet filter flexibly;<br/> Specialized design for system breakdown prevention to maintain stable system;<br/> Support dynamic distance calculation on EMS online;<br/> Support RSTP,IGMP Proxy.</p> |

## CX600G1

| Item                  |                     | CX600G1  |
|-----------------------|---------------------|--|
| Dimension(L*W*H)      |                     | 442mm*200mm*43.6mm                                     |
| Weight                |                     | 3.1kg  |
| Power Supply          | 220VAC              | AC:90~264V, 47/63Hz;<br>Double Power Module/Hot Backup |
| Power Consumption     |                     | 25W  |
| Operating Environment | Working Temperature | -10~+55°C  |
|                       | Storage Temperature | -40~+85°C  |
|                       | Relative Humidity   | 5~90%(non-conditioning)                                |

## Product appearance features

